

3. Dimensions

◆ Deluxe / Standard Plus (SK Chassis)

S3NM18KL1ZA [DC18RQ NSK], S3NM18KL2FA [PC18SQ NSK], S3NM24K21ZA [DC24RQ NSK], S3NM24K22FA [PC24SQ NSK], S3NM18KL3FA [S18ET NSK], S3NM24K23FA [S24ET NSK]

[Unit: mm]
Chassis code : SK
DWG No. : TBJ36794501_Rev01

3D VIEW

Top View

Side View

Front View

Rear View

Fixing the installation plate, drilling hole

Approx. 475 to gas pipe
Approx. 365 to liquid pipe
Approx. 310 to drain hose

Connecting gas/liquid pipe, drain hose

In case of left side piping

Unit Outline

Note

- Unit should be installed in compliance with the installation manual in the product box.
- Unit should be grounded in accordance with the local regulations or applicable national codes.
- All electrical components and materials to be supplied from the site must comply with the local regulations or international codes.
- Electric characteristics chapter should be considered for electrical work and design. Especially the power cable and circuit breaker should be selected in accordance with that.

Symbols

- Piping Direction
- Datum line

No.	Part Name	Description
6	Decoration Cover	-
5	Display & Remote Controller Signal Receiver	-
4	Terminal Block for Power Supply Communication	-
3	Drain hose connection	-
2	Installation Plate	-
1	Refrigerant/Drain pipe and cable routing hole	Knock-out type